

CERINȚE MINIME	
Tip	Sistem sonorizare AMC pentru magazine/cafelele mici, difuzor plafon, amplificator, cabluri
Specificatii Tehnice amplificator 60W – 1 buc	
Putere iesire	60W
Sursa de alimentare	230V AC, 50Hz sau 24V DC
Conectivitate	
Iesire	Conector Phoenix (impedanta joasa 4Ω) Conector Phoenix (impedanta mare 100V) RCA stereo (iesire de linie)
Intrare	MIC inputs: • Sensibilitate: -45 dBu • Conector: MIC 1 – Phoenix • Prioritate: Doar MIC 1, comutabil • Alimentare Phantom: Doar MIC 1, 24V DC, comutabila AUX input • Iesire cu impedanta joasa: 4Ω (conector Phoenix) • Iesire cu impedanta mare: 100V (conector Phoenix) • Iesire de linie: RCA stereo
Consum satnd by	13.6VA
Consum AC	120VA
Consum DC	106VA
Tensiune alimentare phantom	24V
Distorsiuni armonice totale	<0.4 %
Raport semnal/zgomot (S/N)	80dB (line) 75 dB (mic)
Raspuns in frecventa	80Hz - 19kHz
Egalizator	Bass: 140Hz +/-10dB Inalte: 16kHz +/-10dB
Dimensiune produs	204x210x44mm
Greutate produs	2.47kg
Difuzoare profesionale de plafon – 4 buc	
Putere	25W (16Ω)
Praguri de putere transformator	15W 7.5W 3.75W
SPL maxim	101dB
Frecventa	80Hz-20kHz
Dispersie la 1000Hz	120° conic
Dimensiun woofer	5" (130mm)
Dimesiune tweeter	0.5" (13mm)
Dimensiune produs	Ø 200x70mm
Greutate produs	1.1kg

Material	Plastic, grilaj magnetic
Culoare	Alb (RAL9016)
Cabluri profesionale de interior - 100m	
Tip	Analog
Material invelis	PVC
Conductori interiori (audio)	2
Diametru conductor interior	Ø 0.98mm
AWG (audio)	18
Conductori audio de cupru	24
Temperatura functionare	-20°C pana la 70°C