

CERINȚE MINIME	
Tip	Sistem sonorizare AMC pentru magazine/cafelele medii, difuzor plafon, amplificator si cabluri incluse
Specificatii Tehnice amplificator 120W – 1 buc	
Putere iesire	120W
Sursa de alimentare	230V AC, 50Hz sau 24V DC
Conectivitate	
Iesire	Conector Phoenix (impedanta joasa 2Ω) Conector Phoenix (impedanta mare 100V) RCA stereo (iesire de linie)
Intrare	MIC inputs: - Sensibilitate: -45 dBu - Conector: MIC 1 – Phoenix - Prioritate: Doar MIC 1, comutabil - Alimentare Phantom: Doar MIC 1, 24V DC, comutabila AUX input - Iesire cu impedanta joasa: 4Ω (conector Phoenix) - Iesire cu impedanta mare: 100V (conector Phoenix) - Iesire de linie: RCA stereo
Consum stand by	16VA
Consum AC	160VA
Tensiune alimentare phantom	24V
Distorsiuni armonice totale	<0.4 %
Raport semnal/zgomot (S/N)	80dB (line) 75dB (mic)
Raspuns in frecventa	80Hz - 19kHz (100V) 20Hz - 20kHz 2Ω
Egalizator	Bass: 140Hz +/-7.5dB Inalte: 16kHz +/-10dB
Dimensiune produs	320x210x44mm
Greutate produs	3.34kg
Difuzoare profesionale de plafon – 6 buc	
Putere	35W (16Ω)
Praguri de putere transformator	25W 12.5W 6.25W
SPL maxim	105dB
Frecventa	60Hz-20kHz
Dispersie la 1000Hz	120° conic
Dimensiun woofer	8" (200mm)
Dimesiune tweeter	0.5" (13mm)
Dimensiune produs	Ø 250x95mm
Greutate produs	1.7kg

Material	Plastic, grilaj magnetic
Culoare	Alb (RAL9016)
Cabluri profesionale de interior - 150m	
Tip	Analog
Numar de canale audio	1
Material invelis	PVC
Conductori interiori (audio)	2
Diametru conductor interior	Ø 0.98mm
AWG (audio)	18
Conductori audio de cupru	24
Temperatura functionare	-20°C pana la 70°C