

CERINȚE MINIME	
Tip	Sistem sonorizare AMC pentru magazine/cafelele mari, difuzor plafon, amplificator si cabluri
Specificatii Tehnice amplificator 240W – 1 buc	
Putere iesire	240W
Sursa de alimentare	230V AC, 50Hz sau 24V DC
Conectivitate	
Iesire	Conector Phoenix (impedanta joasa 2Ω) Conector Phoenix (impedanta mare 100V) RCA stereo (iesire de linie)
Intrare	MIC inputs: - Sensibilitate: -45 dBu - Conector: MIC 1 – Phoenix - Prioritate: Doar MIC 1, comutabil - Alimentare Phantom: Doar MIC 1, 24V DC, comutabila AUX input - Iesire cu impedanta joasa: 4Ω (conector Phoenix) - Iesire cu impedanta mare: 100V (conector Phoenix) - Iesire de linie: RCA stereo
Consum stand by	19VA
Consum AC	320VA
Tensiune alimentare phantom	24V
Distorsiuni armonice totale	<0.4 %
Raport semnal/zgomot (S/N)	80dB (line) 75dB (mic)
Raspuns in frecventa	80Hz - 19kHz (100V) 20Hz - 20kHz 2Ω
Egalizator	Bass: 140Hz +/-7.5dB Inalte: 16kHz +/-10dB
Dimensiune produs	350x210x44mm
Greutate produs	4.62kg
Difuzoare profesionale de plafon– 8 buc	
Tip	Difuzor de plafon
Putere	35W (16Ω)
Praguri de putere transformator	25W 12.5W 6.25W
SPL maxim	90dB
Frecventa	60Hz-20kHz
Dispersie la 1000Hz	120° conic
Dimensiun woofer	8" (200mm)
Dimesiune tweeter	0.5" (13mm)
Dimensiune produs	Ø 250x95mm

Greutate produs	1.7kg
Material	Carcasa din plastic Grilaj din otel
Culoare	Alb (RAL9016)
Cabluri profesionale de interior - 200m	
Tip	Analog
Numar de canale audio	1
Material invelis	PVC
Conductori interiori (audio)	2
Diametru conductor interior	Ø 1.38mm
AWG (audio)	16
Conductori audio de cupru	84
Temperatura functionare	-30°C pana la 70°C