

CERINȚE MINIME	
Tip	Pupitru conferinta cu sistem interactiv
Specificatii tehnice display	
Diagonala	21.5"
Timp de raspuns	Maximum 14ms
Raport de aspect	16:9
Suprafata de afisare	476.064(H)×267.786(V)
Rezolutie	Minimum 1920x1080pixeli
Distanta dintre pixeli	0.24795×0.24795
Refresh	60Hz
Culori	16.7M (8bit)
Contrast	Minimum 1000:1
Unghi de vizualizare	178°(H/V)
Unitatea de iluminare din spate	ELED
Luminozitate	Minimum 450cd/m ²
Durata de viata a ecranului	Minimum 30000ore
Specificatii tehnice Sistem Tactil	
Tip de detectare	Detectare capacitiva
Instrument de atingere	Deget, pen activ
Dimensiunea minima a obiectului	6mm
Puncte de atingere	Minimum 10
Respingererea palmelor	Suport
Specificatii tehnice microfon	
Microfoane	Minimum 2
Distanta de preluare	0~0.30m
Specificatii tehnice Modul Wireless	
Versiune	802.11 a/b/g/n/ac
Frecventa de operare	5GHz; 2.4GHz
Distanta	0~10m
Partajare wireless a ecranului	
Modul de operare	AP
Frecventa de operare	5GHz
Conectivitate	Minimum 1x Intrare HDMI; Minimum 1x Iesire HDMI; Minimum 3x USB 2.0; Minimum 1x RJ45 10/100/1000 Mbps; Minimum 1x AC IN; Minimum 1x DC IN 19V/6.31A; Minimum 2x Intrari Microfon (Gooseneck); Minimum 1x Iesire Audio 6.5mm; Minimum 2x Iesiri Audio 3.5mm;

	Minimum 1x lesire Audio Cannon/XLR; Minimum 1x Intrare Audio 3.5mm; Butoane fizice: Minimum 4x Butoane (Buton de pornire, Deplasare in sus, Deplasare in jos, Mute).
Dimensiune	Maximum 787×420×1011mm (L×H×D)
Roti	Minimum 2x Roti
Greutate	Maximum 30kg
Accesorii incluse	Cablu de alimentare, Cablu HDMI, Adaptor cablu HDMI, Adaptor cablu casti, Smart Pen, 2x Microfoane Gooseneck
Temperatura de functionare	Minimum intervalul 0°C~40°C
Model PC	OPS72C(Windows 10 IoT Enterprise)
CPU	Minimum i5-1240P(1.7GHz)
RAM	Minimum 16GB
ROM	Minimum 256GB
Tensiune de alimentare	100-240V~ 50/60Hz 2.0A/19VDC 6.3A
Consum de energie	Maximum 120W
Garantie	Minimum 2ani