

DATA SHEET

DESONO™ MASK6C

TWO-WAY 6.5-INCH SURFACE MOUNT LOUDSPEAKER



APPLICATIONS

Bars and Restaurants · Hotels · Casinos
Retail Outlets · Health and Fitness Clubs
Houses of Worship · Exhibit Halls
Corporate Meeting Rooms

DESCRIPTION

The Desono MASK6C two-way, 6.5" surface mount loudspeaker delivers crystal clear sound for all your public address and background music needs. Available in black or white, its 6.5" coated paper cone woofer and a 1" silk dome tweeter results in a high SPL and extremely low distortion, ensuring unprecedented clarity over the entire frequency spectrum.

Designed with the installer in mind, the MASK6C ships with the patented ClickMount bracket, enabling all audio connections to be made at the bracket itself. Pre-defined horizontal and vertical notches in the bracket make loudspeaker adjustments fast and repeatable. To complete the installation, simply 'click' the loudspeaker in place.

The Desono MASK6C is designed for outdoor applications such as patios or concourses, and an ideal choice for both indoor and outdoor distributed audio applications that demand superior speech intelligibility and full range music reproduction.

FEATURES

- Zoom Certified
- IP64 rated for outdoor applications such as patios or concourses
- Waterproof connector sealing for outdoor applications
- Innovative ClickMount™ bracket allows all audio connections to be made at the bracket
- Integrated spirit level for fast, hassle-free positioning and mounting
- Loudspeaker overload protection for 24/7 failsafe operation

zoom Certified

TECHNICAL SPECIFICATIONS

Operating Mode	Passive	
Operating Environment	Indoor/Outdoor	
Operating Range (-10dB)	65 Hz to 22 kHz	
Nominal Beamwidth (H x V)	100° x 50°	
Transducers	LF 1 x 6.5" (165 mm) coated paper cone HF 1 x 1" (25 mm) soft dome	
Continuous Power Handling @ Nominal Impedance	35V	150W @ 8Ω (600W peak)
Nominal Sensitivity @ 1m	@ 1W 89 dB	@ 2.83V 89 dB
Nominal Maximum SPL @ 1m	Peak 117 dB	Continuous 111 dB
Protection	3-step self-resetting protection	
Recommended Amplifiers	150W - 300W @ 8Ω (35V - 49V)	

PHYSICAL

Input Connection	Audio connections made at the ClickMount bracket; lever-action input and output terminals accept up to 16 AWG conductors
Mounting Provisions	ClickMount bracket
Environmental	IP64 per IEC 60529
Dimensions H x W x D	12.9" x 7.8" x 7.5" (328 mm x 198 mm x 190 mm)
Weight	9.7 lbs (4.4 kg)
Finish	Refer to the Technical Drawings (page 3)
Accessories (included)	ClickMount bracket; safety cable

OPTIONS

Accessories	MASKCL(-BL/-W): 90° mounting bracket, black/white MASKCV(-BL/-W): 2-cluster mounting bracket, black/white MASKCW(-BL/-W): 4-cluster mounting bracket, black/white
-------------	---


Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Data presented on this spec sheet represents the basic performance specifications for the model. For a detailed analysis of this loudspeaker's performance, please download the GLL file from our website: biamp.com


DESONO MASK6C

TWO-WAY 6.5-INCH
SURFACE MOUNT LOUDSPEAKER


FREQUENCY RESPONSE (dB SPL)




HORIZONTAL OFF-AXIS RESPONSE (dB)




IMPEDANCE (Ohms)




VERTICAL OFF-AXIS UP RESPONSE (dB)



BEAMWIDTH (Degrees)



VERTICAL OFF-AXIS DOWN RESPONSE (dB)



DESONO MASK6C

TWO-WAY 6.5-INCH
SURFACE MOUNT LOUDSPEAKER

TECHNICAL DRAWING / DIMENSIONS / FINISH

H x W x D

12.9" x 7.8" x 7.5"
(328 mm x 198 mm x 190 mm)

Unit Weight

9.7 lbs (4.4 kg)

Shipping Weight

10.8 lbs (4.9 kg)

Grille:

Aluminum

White (RAL 9016) or Black (RAL 9011) finish

Enclosure / Finish

ABS plastic, matte finish, White or Black

